

Target point 



DKP301

DESKTOP SCANNER

RELIABLE SCANNING
HIGH PERFORMANCE



Supermarket



Payment



Self-order



Mall



Checkout



Parking

📍 1F, 23, Dosan-daero
35-gil, Gangnam-gu,
Seoul, Republic of Korea

☎ +82-2-323-3028

✉ info@targetpoint.co.kr

📞 +82-10-4717-7792



Datasheet

Performance		
Image sensor		CMOS
Resolution		640*800
Illumination		white LED
Aiming		Red LED
Scannig mode		Sense mode
Symbologies	2D	PDF417、MicroPDF417、MicroQR、Data Matrix、QR、Aztec
		EAN-8、EAN-13、EAN-13 2 add-on、EAN-13 5 add-on、ISSN、ISBN、UPC-A、UPC-E、Code11、Code 32、Code 39、Code 39FULLASCII、Code 93、Code 128、Codabar、Industrial 2 of 5、Interleaved 2 of 5、Matrix 2 of 5、GS1-128、GS1 DataBar (RSS14)、GS1 DataBar Limited、GS1 DataBar Expanded
	1D	
	Code39 (5mil)	30mm~60mm
	UPC/ENA 100%	10mm~160mm
	Code39 (20mil)	40mm~220mm
	QR code (20mil)	10mm~140mm
Min Print Contract*		≥20%
Min. resolution		Code 39 4 mil
Motion tolerance		3.2M/S
Scan angles		tilt: 360°, pitch: ±60°, skew: ±70°
Electronic		
Interface		USB, USB-COM,RS232
Dimension(mm)		98mm*98mm*142mm
Weight		364g (not include cable)
Input Voltage		5VDC±10%
Working Current		130~405 mA
Environmental		
Operating Temperature		-20℃~+50℃
Storage Temperature		-20℃~+55℃
Humidity		5%~95% (Non-Condensing)
ESD		±8kV (air discharge), ±4kV (direct discharge)
IP Rating		IP54
*Test conditions: Ambient temperature=23 °C; Ambi *Test conditions: Ambient temperature *Test conditions: Ambient temperature=23 °C; Ambient illumination=300 LUX incandescent lamp		
*Performance may be impacted by barcode quality *Performance may be impacted by bar *Performance may be impacted by barcode quality and environmental conditions.		

