

Target point



S21

Handheld Scanner

RELIABLE SCANNING
HIGH PERFORMANCE



Supermarket



Warehouse



Self-order



Mall



Logistics



QR payment

📍 1F, 23, Dosan-daero
35-gil, Gangnam-gu,
Seoul, Republic of Korea

☎ +82-2-323-3028

✉ info@targetpoint.co.kr

📞 +82-10-4717-7792



Datasheet

Performance		
Image sensor		CMOS
Resolution		640*800
Illumination		620nm red LED
Symbologies	2D	QR Code: Datamatrix, PDF417, Micro QR, Micro PDF417, Support code on screen
		EAN13, EAN8, UPCA, UPC-E0, UPC-E1, Code128, Code39, Code93, Interleaved 2 of 5, Industrial 25, Matrix 2 of 5, Code11, CodaBar, MSI, RSS
	1D	
Typical Decode Range*	EAN-13 (13mil)	50mm~340mm
	Code39 (5mil)	35mm~160mm (barcode: 10mm*6mm)
	Datamatrix (10mil)	35mm~180mm
	QR Code (10mil)	30mm~150mm
	PDF417 (10mil)	30mm~210mm
Min Print Contract*		≥20%
FOV		Horizontal 48°, Vertical 30°
Electronic		
Interface		USB, USB-COM,RS232
Dimension(mm)		159(W)×65.5(D)×85(H)
Weight		120g (not include cable)
Input Voltage		5VDC±10%
Working Current		92~154 mA
Environmental		
Operating Temperature		0℃~+50℃
Storage Temperature		-20℃~+70℃
Humidity		5%~95% (Non-Condensing)
ESD		±8kV (air discharge), ±4kV (direct discharge)
IP Rating		IP52
*Test conditions: Ambient temperature=23 °C; Ambient illumination=300 LUX incandescent lamp		
*Performance may be impacted by barcode quality *Performance may be impacted by bar *Performance may be impacted by barcode quality and environmental conditions.		

